

## How to Use Quickwood:

**QuikWood** Epoxy Putty Stick is a hand-kneadable, fast-setting polymer compound for permanent repairs to wood. It also bonds to metal, glass, masonry and many plastics. It comes in a handy "Tootsie-roll<sup>®</sup>" form with the curing agent encapsulated in the contrasting color base material. Color: Neutral

### How to use:

Before applying, roughen and clean area to be repaired. Then follow these easy steps.



1. Cut off required amount.



2. Mix to uniform color.



3. Apply to repair surface within 10 minutes.

Original QuikWood has a 15 to 25 minute work life. Fast-Cure Pine and Dark have a 3 to 6 minute work life and must be applied within 2 minutes of mixing. Functional cure occurs in 60 minutes. QuikWood is not intended for structural applications.

### Benefits:

- Will not shrink or pull away.
- Cured hardness and density are similar to that of wood.
- Putty-like consistency eliminates drips and runs for a "no mess" application.
- No tools required for use.
- One hour after application can be drilled, sawed, sanded, filed, tapped, machined, and painted.
- Original QuikWood conforms to ASTM D-4236.

### Typical applications:

- Fill scratches, gouges, cracks, dry rot, insect damage and knotholes.
- Repair furniture, molding and frames.
- Reshape woodcarvings.
- Mold wood knobs and handles.
- Can be sculpted or carved for intricate detail.
- Hobby and crafts.



Restore gouges in picture frames.